NSN 3120-01-119-2084

Sleeve Bushing - Page 1 of 1

Mil-s-6758 spec.



View Online at https://aerobasegroup.com/nsn/3120-01-119-2084
Overall Length:
Between 0.4265 inches and 0.4365 inches
Body Outside Diameter:
Between 0.4380 inches and 0.4385 inches
Body Inside Diameter:
Between 0.3050 inches and 0.3070 inches
Flange Outside Diameter:
Between 0.6200 inches and 0.6300 inches
Flange Width:
Between 0.0575 inches and 0.0625 inches
Corner Shape:
Square outside right corner
Hardness Rating:
33.0 rockwell c and 37.0 rockwell c
Surface Finish:
200.0 microinches inside diameter surface of body
Material:
Steel comp 4130 or steel comp 4140 or steel comp e4340
Material Specification:
Mil-s-6758, c4 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-5000, cond
military specification 3rd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Style Designator:
22c solid, external flange one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):