

View Online at <https://aerobasegroup.com/nsn/3120-01-120-0997>

Casehardening Indicator:

Not casehardened

Counterbore Diameter:

Between 0.395 inches and 0.405 inches

Counterbore Depth:

Between 0.050 inches and 0.060 inches

Outside Diameter:

Between 0.498 inches and 0.502 inches

Metallic Hardness Rating:

33.0 rockwell c and 38.0 rockwell c

Face Width:

Between 0.270 inches and 0.290 inches

Bore Inside Diameter:

Between 0.301 inches and 0.303 inches

Chamfer/radius Of Outside Corner:

0.020 in. Min, 0.040 in. Maximum radius

Special Features:

Bore inside diameter relieved to 0.321 in. Min, 0.343 in. Maximum diameter by 0.010 in. Min, 0.020 in. Maximum length

Material:

Steel alloy, astm a322, comp 4140 or steel alloy, astm a322, comp 4140 or steel alloy, astm a331, comp 4140 or steel alloy, astm a331, comp 4140

Material:

Steel alloy, astm a322, comp 4140 or steel alloy, astm a322, comp 4140 or steel alloy, astm a331, comp 4140 or steel alloy, astm a331, comp 4140

Surface Treatment:

Phosphate, dod-p-16232, type m, class 1 or phosphate, dod-p-16232, type z, class 1

Style Designator:

Plain, counterbored

Surface Treatment:

Phosphate, dod-p-16232, type m, class 1 or phosphate, dod-p-16232, type z, class 1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T267-k