## NSN 3120-01-123-7890

Sleeve Bushing - Page 1 of 1



20-01-123-7890

| View Online at https://aerobasegroup.com/nsn/312   |
|--|
| Overall Length:  |
| Between 0.9300 inches and 0.9550 inches  |
| <b>Body Outside Diameter:</b>  |
| Between 0.6110 inches and 0.6140 inches  |
| Body Inside Diameter:  |
| Between 0.5015 inches and 0.5020 inches  |
| Flange Outside Diameter:   |
| 1.6200 inches  |
| Flange Width:  |
| Between 0.0570 inches and 0.0620 inches  |
| End To Flange Distance:  |
| Between 0.0780 inches and 0.0880 inches  |
| Corner Shape:  |
| Square outside right corner  |
| Hardness Rating:   |
| 34.0 rockwell c and 38.0 rockwell c  |
| Surface Finish:  |
| 63.0 microinches outside diameter surface of body  |
| Left End Body Diameter:  |
|  |
| Between 0.6265 inches and 0.6270 inches  |
| Between 0.6265 inches and 0.6270 inches  Special Features:   |
|  |
| Special Features:  |
| Special Features: Insert, stainless steel 17-4ph   |
| Special Features: Insert, stainless steel 17-4ph Material:   |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630   |
| Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification:  |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response  |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response Surface Treatment:   |
| Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate   |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:  |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response  |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator:  |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange               |
| Special Features: Insert, stainless steel 17-4ph  Material: Steel comp 630  Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange Shelf Life:   |
| Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange Shelf Life: N/a |
| Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange Shelf Life: N/a |

Fiig:

A045a0