NSN 3120-01-123-7890

Sleeve Bushing - Page 1 of 1



20-01-123-7890

View Online at https://aerobasegroup.com/nsn/312
Overall Length:
Between 0.9300 inches and 0.9550 inches
Body Outside Diameter:
Between 0.6110 inches and 0.6140 inches
Body Inside Diameter:
Between 0.5015 inches and 0.5020 inches
Flange Outside Diameter:
1.6200 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
End To Flange Distance:
Between 0.0780 inches and 0.0880 inches
Corner Shape:
Square outside right corner
Hardness Rating:
34.0 rockwell c and 38.0 rockwell c
Surface Finish:
63.0 microinches outside diameter surface of body
Left End Body Diameter:
Between 0.6265 inches and 0.6270 inches
Between 0.6265 inches and 0.6270 inches Special Features:
Special Features:
Special Features: Insert, stainless steel 17-4ph
Special Features: Insert, stainless steel 17-4ph Material:
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification:
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment:
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator:
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange Shelf Life:
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange Shelf Life: N/a
Special Features: Insert, stainless steel 17-4ph Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Bac 5751, 77272 mfr ref single treatment response Style Designator: 21c solid, external flange Shelf Life: N/a

Fiig:

A045a0