

View Online at <https://aerobasegroup.com/nsn/3120-01-131-5538>

Bore Diameter:

Between 0.8745 inches and 0.8750 inches

Outer Member Outside Diameter:

Between 1.6245 inches and 1.6250 inches

Outer Member Width:

Between 0.7550 inches and 0.7600 inches

Inner Member Width:

Between 0.7750 inches and 0.7800 inches

Static Radial Load Rating:

116000 pounds

Special Features:

Outer race member notched two places for insertion and removal of inner race member; 0.9410 in. Min, 0.9430 in. Maximum sleeve length, pressed into bore of inner race member

Test Data Document:

81349-mil-std-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-std-1949 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0