# NSN 3120-01-132-2232

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-132-2232

# **Overall Length:**

Between 0.4520 inches and 0.4670 inches

# Body Outside Diameter:

Between 0.5006 inches and 0.5013 inches

# Body Inside Diameter:

Between 0.3750 inches and 0.3765 inches

# Flange Outside Diameter:

Between 0.6150 inches and 0.6350 inches

## Flange Width:

Between 0.0570 inches and 0.0620 inches

# Corner Shape:

Undercut left flange body corner

# Surface Finish:

100.0 microinches

## Material:

Copper alloy 642 or copper alloy 630

# Material Specification:

Qq-c-465 federal specification 1st material response or mil-b-6946 military specification 2nd material response or ams 4640 assn standard

2nd material response

## Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

#### Style Designator:

22c solid, external flange one end

#### **Specification Data:**

80205-nas77 professional/industrial association standard

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A045a0

## Mil-std (military Standard):

Mil-b-6946 spec.