

View Online at <https://aerobasegroup.com/nsn/3120-01-132-8652>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

6.8100 inches

Bore Diameter:

Between 1.7498 inches and 1.7503 inches

Outer Member Outside Diameter:

2.4600 inches

Bore Center To Shank End Distance:

5.5800 inches

Outer Member Width:

Between 0.7920 inches and 0.8920 inches

Inner Member Width:

Between 0.9980 inches and 1.0000 inches

Shank End To Shoulder Length:

3.8900 inches

Shank Thread Length:

0.2540 inches

Special Features:

Ytwo coats of paint except on od of race insert; shank and shoulder not painted; 1.4375-12, series unj, class 3a threads, 0.960 in. Lg, on od of shoulder; 0.6560 in. Min and 0.6610 in. Maximum diameter x 0.4400 in. Lg extension on bottom of shank

Test Data Document:

76301-ps-21201, class a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76301-ps-21202, class a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0