

View Online at <https://aerobasegroup.com/nsn/3120-01-134-8696>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

3.1065 inches

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Outer Member Outside Diameter:

1.3370 inches

Bore Center To Shank End Distance:

Between 2.4280 inches and 2.4480 inches

Outer Member Width:

Between 0.5100 inches and 0.5200 inches

Inner Member Width:

Between 0.6230 inches and 0.6250 inches

Shank Thread Length:

Between 1.4370 inches and 1.4990 inches

Static Radial Load Rating:

19500 pounds

Thread Diameter:

0.5000 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

55.0 rockwell c inner member

Material:

Steel comp 630 rod end body

Material Specification:

Karon, fscm 50632 mfr ref single material response race liner

Surface Treatment:

Ceramic race liner

Surface Treatment Specification:

Karamite, fscm 50632 mfr ref single treatment response race liner

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0