

View Online at <https://aerobasegroup.com/nsn/3120-01-135-7330>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

3.5600 inches

**Bore Diameter:**

Between 0.3120 inches and 0.3125 inches

**Outer Member Outside Diameter:**

1.1200 inches

**Bore Center To Shank End Distance:**

3.0000 inches

**Outer Member Width:**

Between 0.3120 inches and 0.3220 inches

**Inner Member Width:**

Between 0.4350 inches and 0.4370 inches

**Shank Thread Length:**

1.3000 inches

**Inspection Hole Center To End Distance:**

0.4400 inches

**Shank Width Across Wrench Flats:**

Between 0.5530 inches and 0.5630 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

55.0 rockwell c inner member and 62.0 rockwell c inner member

**Special Features:**

Four equally spaced slots for locking washer in end of shank; w/o bead on shank

**Material:**

Steel comp 630 race insert

**Surface Treatment:**

Passivate rod end body

**Style Designator:**

Ball type

**Test Data Document:**

76301-ps21201 class b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0