

View Online at <https://aerobasegroup.com/nsn/3120-01-135-7330>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

3.5600 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

1.1200 inches

Bore Center To Shank End Distance:

3.0000 inches

Outer Member Width:

Between 0.3120 inches and 0.3220 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

1.3000 inches

Inspection Hole Center To End Distance:

0.4400 inches

Shank Width Across Wrench Flats:

Between 0.5530 inches and 0.5630 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member

Special Features:

Four equally spaced slots for locking washer in end of shank; w/o bead on shank

Material:

Steel comp 630 race insert

Surface Treatment:

Passivate rod end body

Style Designator:

Ball type

Test Data Document:

76301-ps21201 class b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0