

View Online at <https://aerobasegroup.com/nsn/3120-01-143-5974>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.3250 inches

**Bore Diameter:**

Between 0.3120 inches and 0.3125 inches

**Outer Member Outside Diameter:**

Between 0.8900 inches and 0.9100 inches

**Bore Center To Shank End Distance:**

Between 1.8650 inches and 1.8850 inches

**Outer Member Width:**

Between 0.3220 inches and 0.3320 inches

**Inner Member Width:**

Between 0.4350 inches and 0.4370 inches

**Shank Thread Length:**

Between 1.1560 inches and 1.2180 inches

**Static Radial Load Rating:**

7180 pounds

**Thread Diameter:**

0.3125 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

55.0 rockwell c inner member and 62.0 rockwell c inner member

**Special Features:**

Keyway in shank

**Material:**

Steel comp 630 race insert

**Material Specification:**

Mil-s-5000 military specification single material response race liner

**Surface Treatment:**

Cadmium rod end body and chromate rod end body

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.