

View Online at <https://aerobasegroup.com/nsn/3120-01-160-2219>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.7495 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2515 inches

**Outer Member Outside Diameter:**

Between 0.8650 inches and 0.8850 inches

**Bore Center To Shank End Distance:**

Between 2.2800 inches and 2.3440 inches

**Outer Member Width:**

Between 0.3300 inches and 0.3400 inches

**Inner Member Width:**

Between 0.4790 inches and 0.4840 inches

**Shank Thread Length:**

1.5000 inches

**Static Radial Load Rating:**

3150 pounds

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Special Features:**

Drilled hole in the shank

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium rod end body

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0