## NSN 3120-01-160-4612

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-160-4612

Overall I	Length:
-----------	---------

Between 0.4100 inches and 0.4150 inches

## **Body Outside Diameter:**

Between 0.6150 inches and 0.6350 inches

#### **Body Inside Diameter:**

Between 0.3150 inches and 0.3200 inches

#### Flange Outside Diameter:

Between 0.9300 inches and 0.9500 inches

#### Flange Width:

Between 0.0500 inches and 0.0700 inches

#### **Corner Shape:**

Square outside right corner

#### **Special Features:**

Counter bored flang 0.5000 in. Min. To 0.5200 in. Max. Dia., 0.0250 in. Min. To 0.0350 in. Max. Depth; right end counter bored 0.5400 in. Min. To 0.5600 in. Max. Dia., 0.0550 in. Min. To 0.0650 max. Depth; groove in outside dia. Surface of body 0.0375 in. Nom. Depth, 0.0600 in. Nom. Wide, 0.1925 in. Nom. From right face

#### Material:

Aluminum alloy 6061

## **Material Specification:**

Qq-a-225/8, t6 federal specification single material response or qq-a-200/8 t6 federal specification single material response

## **Surface Treatment:**

Chromate

## **Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response

## Style Designator:

22c solid, external flange one end

## Shelf Life:

N/a

#### **Unit Of Measure:**

## **Demilitarization:**

No

# Fiig:

A045a0

## Mil-std (military Standard):

Mil-c-5541 spec.