NSN 3120-01-162-5770

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-162-5770

Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
Body Outside Diameter: Between 0.6888 inches and 0.6893 inches Body Inside Diameter: Between 0.5400 inches and 0.5450 inches Flange Outside Diameter: 0.9500 inches Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Arms 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: Arms 5643, 17-4 ph single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mill-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	Overall Length:
Between 0.6888 inches and 0.6893 inches Body Inside Diameter: Between 0.5400 inches and 0.5450 inches Flange Outside Diameter: 0.9500 inches Flange Wildth: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 3.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Arms 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-4402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 181349-mil+-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	0.6050 inches
Body Inside Diameter: Between 0.5400 inches and 0.5450 inches Flange Outside Diameter: 0.9500 inches Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left comer Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-402, [scm 77751 mfr ref single treatment response or z-1901 sz, [scm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil+-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	Body Outside Diameter:
Between 0.5400 inches and 0.5450 inches Flange Outside Diameter: 0.9500 inches Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-1402, fscm 77751 mfr ref single treatment response or z-1901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22 cs olid, external flange one end Test Data Document: 81349-mill-16686 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.6888 inches and 0.6893 inches
Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: 32.0 microinches outside diameter surface of body Material: Steet comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-1402, Iscm 77751 mfr ref single treatment response or z-1901 sz, Iscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mill-16868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Inside Diameter:
0.9500 inches Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Between 0.5400 inches and 0.5450 inches
Flange Width: Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-1402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mili-1-8868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Flange Outside Diameter:
Between 0.0600 inches and 0.0650 inches Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-1402, fscm 77751 mfr ref single treatment response or z-1901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-1-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	0.9500 inches
Corner Shape: Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-4402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Flange Width:
Square outside left corner Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-1402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil+i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.0600 inches and 0.0650 inches
Surface Finish: 32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-1402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Corner Shape:
32.0 microinches outside diameter surface of body Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Square outside left corner
Material: Steel comp 630 Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Finish:
Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	32.0 microinches outside diameter surface of body
Material Specification: Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
Ams 5643, 17-4 ph assn standard single material response Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Steel comp 630
Surface Treatment: Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material Specification:
Cadmium and titanium or passivate Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ams 5643, 17-4 ph assn standard single material response
Surface Treatment Specification: F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium and titanium or passivate
Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:
22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	F-t402, fscm 77751 mfr ref single treatment response or z-r901 sz, fscm 77751 mfr ref single treatment response
Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	22c solid, external flange one end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A045a0	Fiig:
	A045a0