

View Online at <https://aerobasegroup.com/nsn/3120-01-163-5958>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 2.2975 inches and 2.3400 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Outer Member Outside Diameter:**

Between 0.8650 inches and 0.9100 inches

**Bore Center To Shank End Distance:**

Between 1.8650 inches and 1.8850 inches

**Outer Member Width:**

Between 0.3390 inches and 0.3490 inches

**Inner Member Width:**

Between 0.5880 inches and 0.5930 inches

**Shank Thread Length:**

Between 1.2500 inches and 1.3400 inches

**Static Radial Load Rating:**

7434 pounds

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Special Features:**

Nas 513 keyway in shank; integral shank not plated

**Material:**

Steel comp 410 outer ring

**Material Specification:**

Nomex, fscm 21335 mfr ref single material response race liner

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0