NSN 3120-01-163-9369

Sleeve Bushing - Page 1 of 1

Mil-s-6050 spec.



| View Online at https://aerobasegroup.com/nsn/3120-01-163-9369 |
|--|
| Overall Length: |
| Between 0.4300 inches and 0.4400 inches |
| Body Outside Diameter: |
| Between 0.3756 inches and 0.3761 inches |
| Body Inside Diameter: |
| Between 0.2380 inches and 0.2430 inches |
| Flange Outside Diameter: |
| Between 0.4900 inches and 0.5100 inches |
| Flange Width: |
| Between 0.0550 inches and 0.0600 inches |
| Corner Shape: |
| Undercut left flange body corner |
| Surface Finish: |
| 63.0 microinches outside diameter surface of body |
| Material: |
| Steel comp 8630 or steel comp 4130 |
| Material Specification: |
| Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response |
| Surface Treatment: |
| Cadmium or chromate |
| Style Designator: |
| 22c solid, external flange one end |
| Specification Data: |
| 80205-nas538 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |