NSN 3120-01-165-2966

Sleeve Bushing - Page 1 of 1

Mil-s-6050 spec.



| View Online at https://aerobasegroup.com/nsn/3120-01-165-2966 |
|--|
| Overall Length: |
| Between 1.8570 inches and 1.8670 inches |
| Body Outside Diameter: |
| Between 0.4381 inches and 0.4386 inches |
| Body Inside Diameter: |
| Between 0.3125 inches and 0.3140 inches |
| Flange Outside Diameter: |
| Between 0.5520 inches and 0.5720 inches |
| Flange Width: |
| Between 0.0570 inches and 0.0620 inches |
| Corner Shape: |
| Undercut left flange body corner |
| Surface Finish: |
| 100.0 microinches intermediate layer |
| Material: |
| Steel comp 4130 or steel comp 8630 |
| Material Specification: |
| Mil-s-6050 military specification single material response or mil-s-6758 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, ty2, cl 2 federal specification single treatment response |
| Style Designator: |
| 22c solid, external flange one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |