

View Online at <https://aerobasegroup.com/nsn/3120-01-165-5834>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

1.8595 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7710 inches and 0.7910 inches

Bore Center To Shank End Distance:

Between 1.4390 inches and 1.4990 inches

Outer Member Width:

Between 0.3370 inches and 0.3470 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

0.7500 inches

Inspection Hole Center To End Distance:

0.3750 inches

Shank Width Across Wrench Flats:

0.4370 inches

Static Radial Load Rating:

5100 pounds

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Lock washer slot in shank

Material:

Stainless steel rod end body

Material Specification:

97613, kahr-lon mfr ref single material response race liner

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0