Rod End Plain Bearing - Page 1 of 2

3b

24





Thread Class: Thread Direction: Right-hand Shank Style: Internally threaded w/hexagon end and inspection hole **Overall Length:** 2.3240 inches **Bore Diameter:** Between 0.3745 inches and 0.3750 inches **Outer Member Outside Diameter:** 1.0240 inches **Bore Center To Shank End Distance:** 1.8120 inches **Outer Member Width:** Between 0.4320 inches and 0.4420 inches **Inner Member Width:** Between 0.4980 inches and 0.5000 inches Shank Thread Length: 1.0000 inches **Inspection Hole Center To End Distance:** 0.4370 inches Shank Width Across Wrench Flats: 0.5620 inches **Static Radial Load Rating:** 13700 pounds **Thread Diameter:** 0.3750 inches Thready Qty Per Inch (tpi): Hardness Rating: 55.0 rockwell c inner member and 62.0 rockwell c inner member **Special Features:** 4slots in bottom of hex end 0.093 in. W, 0.056 deep eq sp Material: Stainless steel rod end body **Material Specification:** Ams 5643 assn standard single material response race insert Style Designator: Ball type **Thread Series Designator:** Unjf

NSN 3120-01-167-7771

Rod End Plain Bearing - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0

