

View Online at <https://aerobasegroup.com/nsn/3120-01-167-7773>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

1.8720 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

0.8060 inches

Bore Center To Shank End Distance:

1.4690 inches

Outer Member Width:

0.3370 inches

Inner Member Width:

0.4370 inches

Shank Thread Length:

0.7500 inches

Inspection Hole Center To End Distance:

0.3745 inches

Shank Width Across Wrench Flats:

0.4370 inches

Static Radial Load Rating:

5500 pounds

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member

Material:

Steel comp 630 race insert

Material Specification:

Mil-s-5000 military specification single material response rod end body

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type1, class2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.