## NSN 3120-01-169-5626

Sleeve Bushing - Page 1 of 1

Mil-std (military Standard):

Mil-s-6758 spec.



View Online at https://aerobasegroup.com/nsn/3120-01-169-5626

View Online at https://aerobasegroup.com/nsn/3120-01-169-5626
Overall Length:
Between 0.2380 inches and 0.2480 inches
Body Outside Diameter:
Between 0.6257 inches and 0.6264 inches
Body Inside Diameter:
Between 0.4930 inches and 0.4950 inches
Flange Outside Diameter:
Between 0.8700 inches and 0.8800 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Square outside right corner
Hardness Rating:
33.0 rockwell c and 37.0 rockwell c
Material:
Steel comp 4130 or steel comp 4140 or steel comp 4340
Material Specification:
Mil-s-6758 military specification 1st material response and mil-s-5626 military specification 2nd material response and mil-s-5000 military
specification 3rd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Style Designator:
22c solid, external flange one end
Specification Data:
26512-gb10c manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0