NSN 3120-01-169-5633

Sleeve Bushing - Page 1 of 1

Surface Treatment Specification:

22c solid, external flange one end

Style Designator:

Unit Of Measure:

Demilitarization:

Shelf Life:

N/a

No Fiig: A045a0



View Online at https://aerobasegroup.com/nsn/3120-01-169-5633 **Overall Length:** Between 0.6400 inches and 0.6470 inches **Body Outside Diameter:** Between 0.6230 inches and 0.6240 inches **Body Inside Diameter:** Between 0.4735 inches and 0.4745 inches Flange Outside Diameter: Between 0.7300 inches and 0.7500 inches Flange Width: Between 0.0600 inches and 0.0620 inches **Corner Shape:** Square all corners **Special Features:** Flange end counterbored 0.4900 in. Min, 0.4940 in. Maximum dia, 0.0600 in. Min, 0.0620 in. Maximum dp; for installation purposes id only shall be dry film lubricated per p.S. 18021, cl 1, with a cetyl alcohol overcoat per p.S. 18015 Material: Copper alloy 173 **Material Specification:** Qq-c-530, cond h federal specification single material response **Surface Treatment:** Cadmium right end surface of left flange and chromate right end surface of left flange

Qq-p-416, type 2, cl 2 federal specification single treatment response right end surface of left flange