NSN 3120-01-169-5635

Sleeve Bushing - Page 1 of 1

Style Designator:

Unit Of Measure:

Demilitarization:

Shelf Life:

N/a

No Fiig: A045a0

22c solid, external flange one end



View Online at https://aerobasegroup.com/nsn/3120-01-169-5635 **Overall Length:** Between 0.6400 inches and 0.6470 inches **Body Outside Diameter:** Between 0.7480 inches and 0.7490 inches **Body Inside Diameter:** Between 0.5935 inches and 0.5945 inches Flange Outside Diameter: Between 0.9280 inches and 0.9480 inches Flange Width: Between 0.0600 inches and 0.0620 inches **Corner Shape:** Square all corners **Special Features:** Flange end counterbored 0.6150 in. Min, 0.6190 in. Maximum dia, 0.0600 in. Min, 0.0620 in. Maximum dp; for installation purposes id only shall be dry film lubricated per p.S. 18021, cl 1, with a cetyl alcohol overcoat per p.S. 18015 Material: Copper alloy 173 **Material Specification:** Qq-c-530, cond h federal specification single material response **Surface Treatment:** Cadmium right end surface of left flange and chromate right end surface of left flange **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response right end surface of left flange