

View Online at <https://aerobasegroup.com/nsn/3120-01-173-0376>

**Hole Diameter:**

0.2500 inches second and 0.2509 inches second

**Overall Length:**

3.2200 inches

**Body Outside Diameter:**

Between 0.9960 inches and 0.9980 inches

**Body Inside Diameter:**

0.5500 inches

**Corner Shape:**

Square outside right corner

**Surface Finish:**

63.0 microinches

**Antirotation/lubrication Type And Quantity:**

2 hole

**Surface Groove Location And Quantity:**

1 external

**Special Features:**

Outside right corner relieved to 0.860 in. Dia, 0.180 in. Long; external groove located 1.245 in. From outside left corner, 0.400 in. Wide, 0.750 in. Dia, double chamfered left corner 0.038 in. Long by 20.0 degrees angle first and 0.210 in. Long by 37.0 degrees angle second, chamfered right corner 0.050 in. Long by 45.0 degrees angle; three counterbores in inner diameter, first counterbore from left inside corner 1.000 in. Deep and 0.870 in. Dia, second counterbore from right inside corner 1.430 in. Deep and 0.675 in. Dia., third counterbore from right inside corner 0.530 in. Deep and 0.7031 in. Dia

**Material:**

Steel uns k44220 or steel uns k44315

**Material Specification:**

Mil-s-8844, class 3 military specification single material response

**Surface Treatment:**

Oil

**Surface Treatment Specification:**

Mil-c-16173, grade 3 military specification single treatment response

**Style Designator:**

17c solid, plain, no outside flanges

**Test Data Document:**

76301-ps21202, class a standard (includes industry or association standards, individual manufactureer standards, etc.). And 76301-ps21205 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-8844 spec