NSN 3120-01-176-1026

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-176-1026

view Offilite at https://aerobasegroup.com/hsr//3120-01-170-1020
Overall Length:
0.3850 inches
Body Outside Diameter:
0.4378 inches
Body Inside Diameter:
0.2509 inches
Corner Shape:
Square all corners
Cubic Measure:
0.07379 cubic inches
Surface Finish:
63.0 microinches outside diameter surface of body
Special Features:
Bore is countersunk on both ends to 62.0 deg. And 0.020 in. Deep; for 416 heat treat to rockwell c35-39 (160, 000-180, 000 psi tensile
strength)per mil-h-6875; for 17-4ph heat treat to cond. H1025 (age harden at 1025 deg. For4 hrs.)per mil-h-6875, part to be free of heat
treatment discoloration or oxidation scale; salt spray and humidity tests are waived for type iv passivation
Material:
Stainless steel
Material Specification:
Ams5643, type 17-4ph, sol tr assn standard single material response or astm a582, type 416, cond. A (cold finished) assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type i, ii, or iii, for17-4ph; type iv for 416 federal specification single treatment response
Style Designator:
17c solid, plain, no outside flanges
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0