NSN 3120-01-176-2487

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-176-2487 **Hole Diameter:** 0.2031 inches first and 0.2091 inches first **Overall Length:** Between 1.2000 inches and 1.2100 inches **Body Inside Diameter:** Between 0.2190 inches and 0.2200 inches Flange Width: 0.2550 inches **End To Flange Distance:** Between 0.2050 inches and 0.2150 inches **Corner Shape:** Square outside right corner Surface Finish: 32.0 microinches internal surfaces **Antirotation/lubrication Type And Quantity:** 2 hole **Surface Groove Location And Quantity:** 1 external Left End Body Diameter: Between 0.3400 inches and 0.3500 inches **Right End Body Diameter:** Between 0.7350 inches and 0.7360 inches **Special Features:** Right inside surface of body counterbored 0.3290 in. Dia, 0.4760 in. Deep; eight sided, irregularlyshaped flange, 1.525 in. O/a height, 0.850 in. O/a width Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9, cond. T7351 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ps 13201, type 2, class 1, fscm 76301 mfr ref 1st treatment response and ps 13208, fscm 76301 mfr ref 2nd treatment response **Test Data Document:** 76301-ps21201, class a standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:**

Fiig: A045a0

No

Demilitarization: