## NSN 3120-01-180-8999

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-180-8999

Overall Length:  0.7600 inches  Body Outside Diameter:  Between 0.8111 inches and 0.8116 inches  Body Inside Diameter:  0.7355 inches  Corner Shape:  Square all corners  Surface Finish:  63.0 microinches outside diameter surface of body  Special Features:  Tapered bore, 0.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
Body Outside Diameter:  Between 0.8111 inches and 0.8116 inches  Body Inside Diameter: 0.7355 inches  Corner Shape: Square all corners  Surface Finish: 63.0 microinches outside diameter surface of body  Special Features:  Tapered bore, 0.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
Between 0.8111 inches and 0.8116 inches  Body Inside Diameter:  0.7355 inches  Corner Shape:  Square all corners  Surface Finish:  63.0 microinches outside diameter surface of body  Special Features:  Tapered bore, 0.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
Body Inside Diameter:  0.7355 inches  Corner Shape: Square all corners  Surface Finish: 63.0 microinches outside diameter surface of body  Special Features: Tapered bore, 0.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
0.7355 inches  Corner Shape: Square all corners  Surface Finish: 63.0 microinches outside diameter surface of body  Special Features: Tapered bore, 0.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
Square all corners  Surface Finish: 63.0 microinches outside diameter surface of body  Special Features: Tapered bore, o.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
Surface Finish: 63.0 microinches outside diameter surface of body Special Features: Tapered bore, o.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner Material:	
63.0 microinches outside diameter surface of body  Special Features:  Tapered bore, o.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner  Material:	
Special Features: Tapered bore, o.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner Material:	
Tapered bore, o.250 in. Basic taper dia. Per 12.000 in. Length; 0.750 in. Nom diameter 0.695 in. From inside right corner	
Material:	
0 470	
Copper alloy 172	
Material Specification:	
Qq-c-530, condition at federal specification single material response	
Style Designator:	
17c solid, plain, no outside flanges	
Test Data Document:	
76301-ps21202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	cation format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments	ronmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A045a0	