# NSN 3120-01-183-1838

Rod End Plain Bearing - Page 1 of 2





## **Thread Class:** 3b **Thread Direction: Right-hand** Shank Style: Internally threaded w/hexagon end and inspection hole **Overall Length:** 2.0720 inches **Bore Diameter:** Between 0.2495 inches and 0.2515 inches **Outer Member Outside Diameter:** 0.7600 inches **Bore Center To Shank End Distance:** Between 1.3020 inches and 1.3220 inches **Outer Member Width:** Between 0.2760 inches and 0.2860 inches **Inner Member Width:** Between 0.3700 inches and 0.3750 inches Shank Thread Length: Between 0.7190 inches and 0.8120 inches **Inspection Hole Center To End Distance:** Between 0.2500 inches and 0.3320 inches Shank Width Across Wrench Flats: Between 0.4380 inches and 0.4980 inches **Thread Diameter:** 0.2500 inches Thready Qty Per Inch (tpi): 28 Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member

### Material:

Steel comp 630 rod end body

#### Style Designator:

Ball type

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

# NSN 3120-01-183-1838

Rod End Plain Bearing - Page 2 of 2

Fiig: A045a0

