

View Online at <https://aerobasegroup.com/nsn/3120-01-185-0627>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.3440 inches

Bore Diameter:

Between 0.2495 inches and 2.5000 inches

Outer Member Outside Diameter:

Between 0.9280 inches and 0.9480 inches

Bore Center To Shank End Distance:

Between 1.8650 inches and 1.8850 inches

Outer Member Width:

Between 0.3380 inches and 0.3480 inches

Inner Member Width:

Between 0.5880 inches and 0.5930 inches

Shank Thread Length:

1.1250 inches

Static Radial Load Rating:

4700 pounds

Thread Diameter:

0.3750 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

56.0 rockwell c inner member

Special Features:

Lubricate race insert per elctrofilm 2396, fscm 73134

Material:

Steel comp 630 rod end body

Surface Treatment:

Chromium inner member

Surface Treatment Specification:

Bms10-70a, type 2, gradea, fscm 73134 mfr ref single treatment response inner member or qq-c-320, class 2 federal specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0