NSN 3120-01-190-2256

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-190-2256

Slot Width:

0.0938 inches first and 0.0950 inches first

Slot Length:

0.0250 inches first and 0.0300 inches first

Overall Length:

Between 0.4140 inches and 0.4240 inches

Body Outside Diameter:

Between 0.3590 inches and 0.3593 inches

Body Inside Diameter:

Between 0.2505 inches and 0.2515 inches

Flange Outside Diameter:

Between 0.5900 inches and 0.6100 inches

Flange Width:

Between 0.0250 inches and 0.0300 inches

Corner Shape:

Square outside right corner

Hardness Rating:

52.0 rockwell c and 56.0 rockwell c

Surface Finish:

32.0 microinches outside diameter surface of body

Antirotation/lubrication Type And Quantity:

1 slot

Special Features:

Eccentricity in bore, 0.2800 in. Min, 0.2900 in. Maximum dia

Material:

Steel comp 440c

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, ty v federal specification single treatment response

Style Designator:

22c solid, external flange one end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0