NSN 3120-01-193-6982

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-193-6982

Overall Length:

0.2520 inches

Body Outside Diameter:

Between 0.6275 inches and 0.6280 inches

Body Inside Diameter:

Between 0.4850 inches and 0.4860 inches

Flange Outside Diameter:

0.8750 inches

Flange Width:

Between 0.0570 inches and 0.0620 inches

Corner Shape:

Undercut left flange body corner

Special Features:

Optional inner layer material-karon, fscm 50632 or fibriloid, fscm 09455

Material:

Steel comp 630 outer layer

Material Specification:

Ams 5643, cond h1025 assn standard single material response outer layer

Surface Treatment:

Passivate outer layer

Surface Treatment Specification:

Ps 13001, fscm 76301 mfr ref single treatment response outer layer

Style Designator:

22c solid, external flange one end

Test Data Document:

76301-ps21202, cl a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A045a0