## NSN 3120-01-193-6983

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-193-6983
Overall Length:
0.3420 inches
Body Outside Diameter:
Between 0.6275 inches and 0.6280 inches
Body Inside Diameter:
Between 0.4850 inches and 0.4860 inches
Flange Outside Diameter:
0.8750 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Undercut left flange body corner
Special Features:
Optional inner layer material-karon, fscm 50632 or fibriloid, fscm 09455
Material:
Steel comp 630 outer layer
Material Specification:
Ams 5643, cond h1025 assn standard single material response outer layer
Surface Treatment:
Passivate outer layer
Surface Treatment Specification:
Ps 13001, fscm 76301 mfr ref single treatment response outer layer
Style Designator:
22c solid, external flange one end
Test Data Document:
76301-ps21202, cl a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A045a0