

View Online at <https://aerobasegroup.com/nsn/3120-01-193-6995>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

2.9185 inches

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Outer Member Outside Diameter:

Between 1.3270 inches and 1.3470 inches

Bore Center To Shank End Distance:

Between 2.2400 inches and 2.2600 inches

Outer Member Width:

Between 0.5100 inches and 0.5200 inches

Inner Member Width:

Between 0.6230 inches and 0.6250 inches

Shank Thread Length:

1.2500 inches

Inspection Hole Center To End Distance:

0.5620 inches

Shank Width Across Wrench Flats:

0.7500 inches

Static Radial Load Rating:

19500 pounds

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

45.0 rockwell c inner member

Special Features:

Furnished w/ 2 seals composed of stainless steel and silicone rubber

Material:

Steel comp 630 rod end body

Material Specification:

Duraliner, fscm 15860 mfr ref single material response race liner

Surface Treatment:

Passivate rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0