## NSN 3120-01-197-1425

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-197-1425

| Overall Length:  |
|--|
| 0.6500 inches  |
| Body Outside Diameter:   |
| Between 0.8142 inches and 0.8152 inches  |
| Body Inside Diameter:  |
| Between 0.6185 inches and 0.6200 inches  |
| Flange Outside Diameter:   |
| 1.1600 inches  |
| Flange Width:  |
| 0.0950 inches  |
| Corner Shape:  |
| Square all corners   |
| Surface Finish:  |
| 32.0 microinches left end surface of body and flange   |
| Special Features:  |
| Left flange right body corner relieved to 0.9800 in. Diameter and 0.0900 in. W   |
| Material:  |
| Steel comp xm-13   |
| Material Specification:  |
| Ams 5629 assn standard single material response  |
| Surface Treatment:   |
| Passivate right end surface of body  |
| Surface Treatment Specification:   |
| Ps 13144, type 2, cl 1, fscm 76301 mfr ref single treatment response outside diameter surface of body  |
| Style Designator:  |
| 22c solid, external flange one end   |
| Test Data Document:  |
| 76301-ps21202, cl a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No Eiler   |
| Fiig:  |
| A045a0   |
|  |