NSN 3120-01-198-8761

Linear-rotary Motion Roller - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-198-8761

| Casehardening Indicator: |
|---|
| Not casehardened |
| Outside Diameter: |
| Between 1.182 inches and 1.192 inches |
| Metallic Hardness Rating: |
| 30.0 rockwell c and 35.0 rockwell c |
| Face Width: |
| Between 0.495 inches and 0.498 inches |
| Bore Inside Diameter: |
| Between 0.375 inches and 0.376 inches |
| Chamfer/radius Of Outside Corner: |
| 0.031 in. By 45 degrees chamfer |
| Material: |
| Steel, astm a304, grade 4140h or steel, od8853, ty d, grade 2, cl b, comp 4140 |
| Material: |
| Steel, astm a304, grade 4140h or steel, od8853, ty d, grade 2, cl b, comp 4140 |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Phosphate, mil-p-16232, type m, class 2 |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T267-k |
| |