NSN 3120-01-200-1484

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-200-1484

^ -					
U١	/eral	ΙLE	≀na	Itn:	

Between 0.2470 inches and 0.2530 inches

Body Outside Diameter:

Between 0.4385 inches and 0.4390 inches

Body Inside Diameter:

Between 0.2869 inches and 0.3019 inches

Flange Outside Diameter:

Between 0.5525 inches and 0.5725 inches

Flange Width:

Between 0.0615 inches and 0.0625 inches

Corner Shape:

Undercut left flange body corner

Hardness Rating:

26.0 rockwell c and 33.0 rockwell c

Surface Finish:

32.0 microinches outside diameter surface of body

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 4130

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Style Designator:

22c solid, external flange one end

Specification Data:

97499-24-007 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0