

View Online at <https://aerobasegroup.com/nsn/3120-01-204-4822>

**Hole Diameter:**

0.1188 inches first and 0.1193 inches first

**Overall Length:**

Between 0.8450 inches and 0.8550 inches

**Body Outside Diameter:**

Between 3.2538 inches and 3.2543 inches

**Body Inside Diameter:**

Between 3.0700 inches and 3.0900 inches

**Left Internal Flange Hole Diameter:**

Between 2.8400 inches and 2.8600 inches

**Left Internal Flange Width:**

Between 0.1200 inches and 0.1300 inches

**Corner Shape:**

Square outside right corner

**Hardness Rating:**

28.0 rockwell c and 38.0 rockwell c

**Surface Finish:**

32.0 microinches outside diameter surface of body

**Antirotation/lubrication Type And Quantity:**

1 hole

**Special Features:**

Lubrication hole located 0.400 in. From right outside corner to center

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4130 or steel

**Material Specification:**

Mil-s-5000 military specification 1st material response or ams 6415 assn standard 2nd material response or mil-t-6736 military specification 3rd material response or ams 6360 assn standard 3rd material response or ems56627, fscm 99137 mfr ref 4th material response

**Style Designator:**

17c-1 solid, plain, no outside flanges, internal flange one end

**Test Data Document:**

99193-ems52308 cl 3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.