

View Online at <https://aerobasegroup.com/nsn/3120-01-204-4822>

Hole Diameter:

0.1188 inches first and 0.1193 inches first

Overall Length:

Between 0.8450 inches and 0.8550 inches

Body Outside Diameter:

Between 3.2538 inches and 3.2543 inches

Body Inside Diameter:

Between 3.0700 inches and 3.0900 inches

Left Internal Flange Hole Diameter:

Between 2.8400 inches and 2.8600 inches

Left Internal Flange Width:

Between 0.1200 inches and 0.1300 inches

Corner Shape:

Square outside right corner

Hardness Rating:

28.0 rockwell c and 38.0 rockwell c

Surface Finish:

32.0 microinches outside diameter surface of body

Antirotation/lubrication Type And Quantity:

1 hole

Special Features:

Lubrication hole located 0.400 in. From right outside corner to center

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4130 or steel

Material Specification:

Mil-s-5000 military specification 1st material response or ams 6415 assn standard 2nd material response or mil-t-6736 military specification 3rd material response or ams 6360 assn standard 3rd material response or ems56627, fscm 99137 mfr ref 4th material response

Style Designator:

17c-1 solid, plain, no outside flanges, internal flange one end

Test Data Document:

99193-ems52308 cl 3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.