

View Online at <https://aerobasegroup.com/nsn/3120-01-204-4839>

Bore Diameter:

Between 0.7495 inches and 0.7500 inches

Lubrication Material:

Grease, mil-g-21164

Outer Member Outside Diameter:

Between 1.4370 inches and 1.4375 inches

Outer Member Width:

Between 0.5880 inches and 0.5930 inches

Inner Member Width:

Between 0.7480 inches and 0.7500 inches

Static Radial Load Rating:

46750 pounds

Hardness Rating:

56.0 rockwell c inner member

Lubrication Feature:

Groove outer race member and perforation outer race member

Material:

Steel comp e4340 outer race member or steel comp 4130 outer race member or steel comp 8630 outer race member

Material Specification:

Mil-s-5000 military specification 1st material response outer race member or mil-s-6758 military specification 2nd material response outer race member or mil-s-6050 military specification 3rd material response outer race member

Surface Treatment:

Cadmium outer race member

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response outer race member

Style Designator:

Without insert or liner with staking groove

Specification Data:

96906-ms21154 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.