Sleeve Bushing - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/3120-01-207-7735



Overall Length:

0.5200 inches

Body Outside Diameter:

Between 1.0838 inches and 1.0843 inches

Body Inside Diameter:

Between 0.9000 inches and 0.9200 inches

Flange Outside Diameter:

Between 1.3700 inches and 1.3900 inches

Flange Width:

Between 0.0850 inches and 0.0950 inches

Corner Shape:

Square all corners

Hardness Rating:

28.0 rockwell c and 34.0 rockwell c

Material:

Steel comp 4130 or steel comp 4340

Material Specification:

Mil-s-6758 military specification 1st material response or mil-t-6736 military specification 1st material response or ams 6371 assn standard 1st material response or ams 6414 assn standard 2nd material response or ams 6415 assn standard 2nd material response or ems 56627, fscm 99193 mfr ref 2nd material response or mil-s-5000 military specification 2nd material response

Style Designator:

22c solid, external flange one end

Test Data Document:

99193-ems52308, class 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life: N/a Unit Of Measure: --Demilitarization:

Demilit

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.