

View Online at <https://aerobasegroup.com/nsn/3120-01-210-1757>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

4.8750 inches

Bore Diameter:

Between 0.7495 inches and 0.7500 inches

Outer Member Outside Diameter:

Between 1.9900 inches and 2.0100 inches

Bore Center To Shank End Distance:

Between 3.8650 inches and 3.8850 inches

Outer Member Width:

Between 0.7450 inches and 0.7550 inches

Inner Member Width:

Between 0.9980 inches and 1.0000 inches

Shank Thread Length:

Between 2.6560 inches and 2.7490 inches

Static Radial Load Rating:

36510 pounds

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Hardness Rating:

55.0 rockwell c inner member

Lubrication Feature:

Self-lubricating liner race liner

Special Features:

Ms14198 keyway in shank, 0.156 in. Wide, 0.098 in. Deep

Material:

Steel comp 630 rod end body

Material Specification:

Qq-s-763 federal specification single material response inner member

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0