NSN 3120-01-212-8638

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-212-8638

Overall Length: 0.3200 inches Body Outside Diameter: Between 0.3760 inches and 0.3765 inches Body Inside Diameter: 0.2500 inches Flange Outside Diameter: 0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Body Outside Diameter: Between 0.3760 inches and 0.3765 inches Body Inside Diameter: 0.2500 inches Flange Outside Diameter: 0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Between 0.3760 inches and 0.3765 inches Body Inside Diameter: 0.2500 inches Flange Outside Diameter: 0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Body Inside Diameter: 0.2500 inches Flange Outside Diameter: 0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
0.2500 inches Flange Outside Diameter: 0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Flange Outside Diameter: 0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
0.5000 inches Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Flange Width: Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Between 0.0610 inches and 0.0620 inches Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Corner Shape: Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Square all corners Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Material: Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Nickel alloy 718 inner layer Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Material Specification: Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Mil-c-83488, class 2, type ii military specification 2nd material response outer layer Style Designator:
Style Designator:
22c solid, external flange one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):
Mil-c-83488 spec.