

View Online at <https://aerobasegroup.com/nsn/3120-01-217-0862>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.0940 inches

**Bore Diameter:**

Between 0.4995 inches and 0.5000 inches

**Outer Member Outside Diameter:**

Between 1.3020 inches and 1.3220 inches

**Bore Center To Shank End Distance:**

Between 2.4280 inches and 2.4480 inches

**Outer Member Width:**

Between 0.5100 inches and 0.5200 inches

**Inner Member Width:**

Between 0.6200 inches and 0.6250 inches

**Shank Thread Length:**

Between 1.4868 inches and 1.5625 inches

**Static Radial Load Rating:**

6600 pounds

**Thread Diameter:**

0.5000 inches

**Thready Qty Per Inch (tpi):**

20

**Lubrication Feature:**

Self-lubricating liner race liner

**Special Features:**

One hole in shank 0.170 in. Deep, 0.370 in. From shank bottom to center for 0.169 in. Diameter plastic locking pellet

**Material:**

Plastic polytetrafluoroethylene race liner

**Material Specification:**

Qq-n-286 federal specification single material response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0