## NSN 3120-01-220-9805

Sleeve Bushing - Page 1 of 1

Mil-s-6050 spec.



View Online at https://aerobasegroup.com/nsn/3120-01-220-9805

View Online at https://aerobasegroup.com/nsn/3120-01-220-9805
Overall Length:
Between 0.6120 inches and 0.6270 inches
Body Outside Diameter:
Between 0.9383 inches and 0.9393 inches
Body Inside Diameter:
Between 0.7495 inches and 0.7500 inches
Flange Outside Diameter:
Between 1.1150 inches and 1.1350 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Undercut left flange body corner
Surface Finish:
100.0 microinches
Material:
Steel comp 8630 or steel comp 4130
Material Specification:
Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Style Designator:
22c solid, external flange one end
Specification Data:
80205-nas77 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):