

View Online at <https://aerobasegroup.com/nsn/3120-01-232-1548>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.9235 inches

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Outer Member Outside Diameter:

1.3470 inches

Bore Center To Shank End Distance:

Between 2.2400 inches and 2.2600 inches

Outer Member Width:

Between 0.3850 inches and 0.3950 inches

Inner Member Width:

Between 0.4980 inches and 0.5000 inches

Shank Thread Length:

Between 1.3820 inches and 1.4020 inches

Static Radial Load Rating:

15500 pounds

Thread Diameter:

0.4375 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

56.0 rockwell c and 62.0 rockwell c inner member

Special Features:

Keyway on shank 0.093 in. Min 0.098 in. Maximum width

Material:

Steel comp 630 rod end body

Material Specification:

Ams 5643 assn standard single material response race insert

Surface Treatment:

Chromium rod end body

Surface Treatment Specification:

Ams 2406 assn standard single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0