

View Online at <https://aerobasegroup.com/nsn/3120-01-232-6337>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 4.3650 inches and 4.3850 inches

Bore Diameter:

Between 0.7495 inches and 0.7515 inches

Outer Member Outside Diameter:

Between 1.9900 inches and 2.0100 inches

Bore Center To Shank End Distance:

Between 3.3650 inches and 3.3850 inches

Outer Member Width:

Between 0.6350 inches and 0.6450 inches

Inner Member Width:

Between 0.8700 inches and 0.8750 inches

Shank Thread Length:

Between 1.8440 inches and 1.9370 inches

Static Radial Load Rating:

82000 pounds

Thread Diameter:

0.8750 inches

Thready Qty Per Inch (tpi):

14

Hardness Rating:

55.0 rockwell c and 60.0 rockwell c rod end body

Material:

Steel comp 630 race insert

Material Specification:

Mil-s-5000 military specification single material response rod end body

Surface Treatment:

Cadmium inner member

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.