# NSN 3120-01-237-1073

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-237-1073

## **Overall Length:**

Between 0.5050 inches and 0.5100 inches

#### **Body Outside Diameter:**

Between 0.5595 inches and 0.5605 inches

#### **Body Inside Diameter:**

Between 0.3745 inches and 0.3760 inches

## Lubricant Accommodation Style:

Grooved circular

#### **Corner Shape:**

Square inside left corner

Surface Finish:

63.0 microinches outside diameter surface of body

## Surface Groove Location And Quantity:

1 external

#### **Functional Description:**

Clamp-up to shaft appl

#### Material:

Steel comp 4130 and steel comp 8630

#### **Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

#### Style Designator:

17c solid, plain, no outside flanges

#### **Specification Data:**

80205-nas73 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

```
--
```

## Demilitarization:

Yes - demil/mli

Fiig:

#### A045a0

Mil-std (military Standard):

Mil-s-6758 spec.