## NSN 3120-01-240-7474

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-240-7474

Overall	Lenath:
Overan	LCHAHI.

Between 0.4330 inches and 0.4380 inches

**Body Outside Diameter:** 

Between 0.5611 inches and 0.5616 inches

**Body Inside Diameter:** 

Between 0.4099 inches and 0.4109 inches

**Corner Shape:** 

Square all corners

**Special Features:** 

Id dry film lubricated, p. S. 18021, class 1 w/acetyl alcohol overcoat, p. S. 18015 for reaming at assembly

Material:

Copper alloy 172 or copper alloy 173

**Material Specification:** 

Qq-c-530 federal specification all material responses

**Surface Treatment:** 

Cadmium right end surface of body and chromate right end surface of body

**Surface Treatment Specification:** 

Qq-p-416, type ii, class 2 federal specification all treatment responses right end surface of body

**Style Designator:** 

17c solid, plain, no outside flanges

## **Test Data Document:**

76301-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A045a0