## NSN 3120-01-244-1145

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-244-1145

| Overall Length:  |
|--|
| 0.3325 inches  |
| Body Outside Diameter:   |
| Between 0.6274 inches and 0.6279 inches  |
| Body Inside Diameter:  |
| Between 0.5000 inches and 0.5015 inches  |
| Flange Outside Diameter:   |
| 0.7500 inches  |
| Flange Width:  |
| Between 0.1850 inches and 0.1950 inches  |
| Corner Shape:  |
| Undercut left flange body corner   |
| Hardness Rating:   |
| 34.0 rockwell c and 38.0 rockwell c  |
| Surface Finish:  |
| 63.0 microinches outside diameter surface of body  |
| Material:  |
| Steel comp e4340   |
| Material Specification:  |
| Mil-s-5000 military specification single material response   |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 3 federal specification single treatment response   |
| Style Designator:  |
| 22c solid, external flange one end   |
| Test Data Document:  |
| 84955-kps 208 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |
| Mil-std (military Standard):   |
|  |

Mil-s-5000 spec.