NSN 3120-01-247-6902

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-247-6902

Overall	Lenath:
Overan	LCHAHI.

Between 0.4640 inches and 0.4690 inches

Body Outside Diameter:

Between 0.5611 inches and 0.5616 inches

Body Inside Diameter:

Between 0.4099 inches and 0.4109 inches

Corner Shape:

Chamfered all corners

Special Features:

Id dry film lubricated, p. S. 18021, class 1 w/acetyl alcohol overcoat, p/ s. 18015 for reaming atassembly

Material:

Copper alloy 172 or copper alloy 173

Material Specification:

Qq-c-530 federal specification all material responses

Surface Treatment:

Cadmium right end surface of body and chromate right end surface of body

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses right end surface of body

Style Designator:

17c solid, plain, no outside flanges

Test Data Document:

76301-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

C	he	Ι£		:£	_
3	пe	ш	_	.11	e.

N/a

Unit Of Measure:

No

Demilitarization:

Fiig:

A045a0